


HDL-DDLA-4

DRAWING (mm)



PHOTO



MODEL NO. DESIGNATION



Example: HDL-DDLA-1

OPTIONAL CONTROL BOX AVAILABLE




GENERAL DATA

Product name	HDL-DDLA-4
Mode	Asynchronous
Number of actuators	4
Compatible control box	DDLA-4
Cable length mm	880 spiral 420
Permissible ambient temperature deg. C	+5°C ~ +40°C
IP	IP20
Connector handset	10P10C (RJ50) Plug
Body material/s	ABS
Color	Pantone cool gray 11C black black spiral cable and connector
Color	Black

CONNECTOR PIN LAYOUT

10P10C (RJ50) Jack



OPERATION GUIDANCE ASYNCHRONOUS CONTROL BOXES

Press and continuously hold down the M button on the handset for actuator/s operation

The actuator/s will stop at any position when the handset button is released

The actuator/s will stop automatically by its internal limit switches at end position

Simultaneous operation of several actuators is possible

CONNECTOR PIN CONFIGURATION

10P10C (RJ50)

1	4 Up M4
2	5V
3	3 Up M3
4	2 Up M2
5	1 Up M1
6	3 Down M3
7	2 Down M2
8	1 Down M1
9	
10	4 Down M4